



**BAKERY EQUIPMENT**  
**BakerSeries Roll-in Proofer**

**SINMAG**  
 Company

Item No. \_\_\_\_\_  
 Project \_\_\_\_\_  
 Quantity \_\_\_\_\_

**MODEL: LRP2S Series**



Model LRP2S-40 Shown (rack not included)

**MODEL / RACK CAPACITY**

Model / Depth	Side Load	End Load	Double
LRP2S-30	2 Racks	3 Racks	None
LRP2S-40	4 Racks	3 Racks	2 Racks
LRP2S-50	4 Racks	3 Racks	2 Racks
LRP2S-60	6 Racks	6 Racks	2 Racks
LRP2S-70	6 Racks	6 Racks	2 Racks
LRP2S-80	9 Racks	6 Racks	4 Racks
LRP2S-90	9 Racks	9 Racks	4 Racks
LRP2S-100	10 Racks	9 Racks	4 Racks
LRP2S-110	10 racks	12 Racks	4 Racks
LRP2S-120	12 Racks	12 Racks	6 Racks

**Short Bid Specification:**

Proofer shall be an **LBC Bakery Equipment Model LRP2S-\_\_** [insert 30,40,50,60,70,80, 90,100, 110, 120] 5 to 13.2 kW electrically heated, double door roll-in rack unit with: quick responding air-wash heat / humidity system; modular foam insulated cam lock panel construction; all 300 series stainless steel interior, with protective cart bumpers; heavy-duty door with magnetic seal/mechanical closure system and full width protective bar handle; simple computerized controls, door mounted at eye-level, with accurate digital temperature, humidity and time readouts; plus all the features listed and options checked.

**Construction Features**

- Heavy duty stainless steel exterior with 300 Series stainless steel interior and aluminized steel top
- Walls Ceilings and doors are foam insulated
- Modular wall and ceiling panels with cam lock construction
- Rapid responding air-wash heat and humidity system
- 208/120 VAC single or 3-phase power, field convertible

**Performance Features**

- 70 - 120 Degree F proofing range
- 50 - 99% humidity range
- Non-submerged calrod type heaters
- Interior bumpers protect interior walls from damage
- CFL Lighted interior

**Controls Features**

- All digital controls mounted in the door at eye-level
- PID Type controls for rapid accurate response without overshoot
- Digital set Temperature, Humidity, Time
- Installed in the left hand door at eye-level
- Large LED displays
- 5 Timers for multiple products



**STANDARD PRODUCT WARRANTY**

One-Year Parts and Labor (contiguous US Including Alaska and Hawaii, Canada)

Sheet Number LRP2S v 1 (rev 1/13)

**Roll-In Proofer**

**MODEL: LRP2S Series**


**INSTALLATION REQUIREMENT**

Ships KD requires on-site installation  
240/120 VAC 1 or 3-phase

1/2" NPT Cold water connection  
3/4" Copper vented drain connection

**OPTIONS & ACCESSORIES**

Stainless Steel Floors Correctional Pack



Model	Depth			Width	Weight		Freight Class
	Internal "A"	Ext. "B"	Over All "C"		Actual	Ship	
LRP2S-30	26.1	31.1	39.3	75.5	1100	1200	85
LRP2S-40	36.1	41.1	49.3	75.5	1157	1282	
LRP2S-50	46.1	51.1	59.3	75.5	1329	1454	
LRP2S-60	56.1	61.1	69.3	75.5	1411	1536	
LRP2S-70	66.1	71.1	79.3	75.5	1493	1618	
LRP2S-80	76.1	81.1	89.3	75.5	1665	1790	
LRP2S-90	86.1	91.1	99.3	75.5	1924	2049	
LRP2S-100	96.1	101.1	109.3	75.5	2006	2131	
LRP2S-110	106.1	111.1	119.3	75.5	2178	2303	
LRP2S-120	116.1	121.1	129.3	75.5	2260	2385	

**Total Electrical Requirements By Model**

Model	Voltage	Total kW	*MCA		*Max Fuse		Water	Drain
			1-Ph	3-Ph	1-Ph	3-Ph		
LRP2- (40-80)	208 VAC	5	30	18	50	50	1/2" NPT .07 GPM @ 60 PSI	1/2"PVC; 210 F; <1 GPM Max.
	240 VAC	6.6	34	20	50	50		
LRP2- (90-120)	208 VAC	10.2	NA	35	NA	60	1/2" NPT .14 GPM @ 60 PSI	1/2"PVC; 210 F; <1 GPM Max.
	240 VAC	13.2	NA	39	NA	60		

*This Appliance is designed to operate at normal room temperatures; Clearance from combustibles is 0.0" sides and back, For Install on non-porous surfaces only*

**\*MCA: Minimum Circuit Ampacity. \*Max Fuse: Maximum allowable circuit protector.**

**IMPORTANT: Your local water conditions may damage your LBC appliance.** Failure to properly treat water may result in damage and may void your warranty. Ensure that your water supply meets these minimum water quality specification.

Parameter	Unit	Value
Alkalinity	ppm	22
Aluminium	ppb	17
Calcium	ppm	3.3
Free Chlorine Residual	ppm	0.6

Parameter	Unit	Value
Magnesium	ppm	0.65
pH	s.u.	8.5
Sodium	ppm	8.5
Total Hardness	ppm	11.9